

Dual-Port Wall-Mounted AC Charger

Commercial EV Charger



Ambient Lighting



Convenient Payment Credit Card, No Hassle



Easy Install/Maintain Access



Easy-to-select Features & Accessories



Seamless Installation Rear Cable Entry Option



Dual-ports Chargers Reduces time by up to 50%

7" touchscreen



Payment solution
powered by Nayax

Ambient Lighting

Easy Options



Ethernet (LAN)



Bluetooth



Wi-Fi



4G



OCPP 1.6J



RFID



Credit Card



CTEP



ISO 15118

MORE+

3-Pieces

Minimalist design, easy assembly

6+ Functions

Easy options, fast Delivery

Tariff savings

TAA/BABA compliant supply solutions, avoid high tariffs.

DATASHEET

Model Number	CNAC-48A*2-RGWB-03-BK	CNAC-80A*2-RGWB-03-BK
Product Type	AC Charging Station	
Input Voltage	208/240V AC, Three-phase	
Input Frequency	50/60 Hz	
Output Voltage	208/240V AC	
Output Current	48A Max x2	80A Max x2
Maximum Power Output	11.5kW x2	19.2kW x2
Input Wire	Hardwired	
Charging Connector Type	2xSAE J1772(Default), NACS Tesla(Optional)	
Cable Length	2x18FT/5.5m Standard (2x25FT/7.5m Optional)	
Charging Modes	Mode3	
Charging Protocols	OCPP 1.6J, OCPP2.0 (upgradable)	
Dimensions (H x W x D)	500*360*176mm(19.7*14.2*6.9inch)	
Weight	33.07lbs (15kg)	46.30lbs (21kg)
Enclosure Rating	NEMA Type3, IK08	
Operating Temperature	-30°C to 50°C(-22°F to 122°F)	
Operating Humidity	<95% Non-condensing	
Altitude	Up to 2000m	
Protection Function	Undercurrent Protectton, Overcurrent Protectton, Undervoltage Protectton, Overvoltage Protectton, Short Circuit Protectton, Residual Current Device, Over Temperature Protectton, Surge Protectton, Ground Fault Protectton, Control Pilot Fault Protectton, Leakage Protectton	
Communication Interface	7Inch Screen, WIFI&Bluetooth/4G	
Control Method	RFID/NFC, POS, OCPP Platform	
Mounting Type	Wall-mounted, Pedestal-mounted	
Compliance Standards	CSA, FCC, Energy Star, CTEP compliance, ISO15118 compliance	
Standards	NEC625,UL817, UL991,UL2231,UL2251,UL2594, OCPP1.6J Compliance	
Warranty Period	2 years	